



Level 2 OCPP EVSE Charger

Cando

Cost-effective, feature-rich Level 2 charger with dynamic load management (**up to 40A**) and time-of-use pricing, delivering top-tier performance.

Quick Facts:

- Level 2 charger, with smart EV charge monitoring and dynamic load balancing for restricted power budgets
- **Flexible load balancing:** 6-40A (Up to 9.6kW) charging output
- Simple wiring with NEMA 14-50 plug
- Allows for wall mounting or single/dual pedestal installation
- Supports OCPP 1.6J
- **Connectivity:** 4G/LTE, WiFi, Ethernet
- **Standards and Certification(s):** Conforms to UL/cUL, FCC, Energy Star



Powerhouse Performance

Delivers up to 9.6kW of power for fast, convenient top ups – ideal for tenants and patrons on the go.

.....



Sleek, Modern Aesthetic

Easy to install, professionally designed EV charging hardware that elevates your property.

.....



Scalable Deployment

Multiple chargers can share a single electrical circuit, minimizing installation for larger deployments.



Level 2 OCPP EVSE Charger

Cando



Data Sheet

Dimensions	H	W	D
	13" (310mm)	9" (220mm)	4" (95mm)
Weight	13.5lbs (6kg) with cable		
Operating Temperature	-22 to 131°F (-30 to 55°C)		
Electrical Ratings	208/240V, Maximum 40A (50A Breaker), 60 Hz		
Cable & Connector	25ft (7.5m) length, J1772 connector		
Enclosure Type	NEMA Type 4		
Connectivity	4G LTE, WiFi, Ethernet		